Benchmark | BMG784

ULTRA LIGHTWEIGHT, EXTREME CUT RESISTANT GLOVES WITH NITRILE FOAM

Using the latest innovation, the BMG784 is a very light weight glove (18 gauge) providing outstanding cut protection and high dexterity in the most risky applications. Thin, breathable with a long lasting coating, ideal for all precise applications.

FEATURES

- Cut resistant: Level F (EN 388:2016)
- 18 gauge seamless liner offers flexibility, comfort and high fingertip sensitivity
- HPPE on the inside provides comfort and protection
- Specific metal fibre and nylon on the outside, fully encapsulated enable extreme cut protection against burrs and sharp edges.
- Nitrile foam coating gives exceptional grip in oily conditions while allowing warm air and moisture from inside to escape, keeping your hands dry and comfortable
- Reinforced thumb crotch enhances durability
- Designed for easy movement and continuous wear
- Breathable back of hand to reduce perspiration
- Seamless knit prevents irritation
- Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Transport

Suitable Applications

- Assembly
- Handling sharp and greasy parts
- Machining
- Bodywork
- Precision mechanics

CERTIFICATION

CAT II

EN 388:2016

4X43F

See overleaf for explanation

Globus GROUP

Benchmark | BMG784

PRODUCT INFORMATION

MATERIALS	LINER:	18 gauge HPPE, metal fiber, nylon
	COATING:	Foam nitrile
COLOUR	Grey/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	ITEM NO.	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	BMG00784ED BMG00784EF BMG00784EH BMG00784EJ BMG00784EL	Individually bagged 10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS
EN 388: 2016

PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

* If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globus.co.uk

E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

© 2020 Globus (Shetland) Ltd | BMK-DATA-BMK784-0620_1

EC compliance certificate delivered by the notified body, SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.