EPIC® MH 4.0mm Contacts

High flexibility by the use of any combination of inserts in one connector

Info
Modular connector system, plugable with the market standard



Robust

Wind Energy

Rail

Mechanical and plant engineering

Kompletterande automationskomponenter från Lapp

Benefits
Crimp connection for permanent vibration proof contact
EPIC® MH system is mateable with the market standard

Application range
Mechanical engineering
Robotics industry
Plant engineering
Renewable energy
Railway applications / vehicle construction

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000796 ETIM 5.0 Class-Description: Contact for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000796 ETIM 6.0 Class-Description: Contact for industrial connectors

Last Update (20.11.2018)
©2018 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® MH 4.0mm Contacts

Contact resistance:	< 5 mOhm
Termination methods:	Crimp termination: 1.5 - 10 mm²
Stripping length (mm):	10
Cycle of mechanical operation:	500

Note
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2018 Lapp Group - Technical changes reserved

LAPP

EPIC® MH 4.0mm Contacts

PRODUCT INFORMATION

Article number	Article description	Contact type	Connection cross section (mm²)
44423250	EPIC® MH SCEM AG 1.5sqmm D=4.0	male	1.5
44423255	EPIC® MH BCEM AG 1.5sqmm D=4.0	female	1.5
44423251	EPIC® MH SCEM AG 2.5sqmm D=4.0	male	2.5
44423256	EPIC® MH BCEM AG 2.5sqmm D=4.0	female	2.5
44423252	EPIC® MH SCEM AG 4sqmm D=4.0	male	4
44423257	EPIC® MH BCEM AG 4sqmm D=4.0	female	4
44423253	EPIC® MH SCEM AG 6sqmm D=4.0	male	6
44423258	EPIC® MH BCEM AG 6sqmm D=4.0	female	6
44423254	EPIC® MH SCEM AG 10sqmm D=4.0	male	10
44423259	EPIC® MH BCEM AG 10sqmm D=4.0	female	10

Last Update (20.11.2018)
©2018 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16