PRODUCT-DETAILS

E 93N/50s

Fuse disconnector



General Information

Extended Product Type	E 93N/50s
Product ID	2CSM256302R1801
EAN	8012542563020
Catalog Description	Fuse disconnector
Long Description	E 90 50/125 fuse holders are appropriate to protect against overloads and short circuits. They are designed for use with cylindrical fuses from 50 to 125 A.

Technical

Suitable For	E 90
Suitable for Product Class	Fuse holders
Rated Voltage (U_r)	acc. To IEC 690 V acc. To UL 690 V
Rated Operational Voltage	AC-20B 690 V
Rated Insulation Voltage (U_i)	1 kV
Rated Frequency (f)	50/60 Hz

© 2024 ABB. All rights reserved.

Subject to change without notice

Power Loss	at Rated Operating Conditions per Pole 5 W
Number of Protected Poles	3
Number of Poles	4P
Position of Neutral Terminals	Right
Tightening Torque	3...3.5 N·m
Utilization Category	Connecting and disconnecting under no-load conditions - occasional actuation (AC-20B)
Lock Type	Padlockable
Mounting Type	DIN-Rail
Sealing Type	Sealing Wire
Material of Conductor	Copper
Options Provided	With LED
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Rigid 2.5…25 mm² Rigid Stranded|2.5…35 mm²
Fuse Size	14x51 mm
	max. 90% with temp. +20 °C|50% with max. temp. +40 °C
Rated Operational Current AC (I_e)	50 A

Material Compliance

RoHS Information	2CSC444009D2701
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	01/01/2014 0.00.00
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Storage -5...+40 °C Storage Operation|-25...+70 °C
Degree of Protection	IP20
Resistance to Vibrations	1 mm 2 … 13 Hz
Resistance to Shock acc. to IEC 60068-2-27	15g 18 shocks 11 ms
Environmental Information	See RoHS Information

Dimensions

Width in Number of Modular Spacings	6
Product Net Width	106.8 mm
Product Net Height	96.5 mm
Product Net Depth / Length	73.26 mm
Product Net Weight	380 g

© 2024 ABB. All rights reserved.

Built-In Depth (t_2)	73.26 mm

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.38 kg
E-Number (Norway)	1416159

Certificates and Declarations

BV Certificate	9AKK108467A0329
CCC Certificate	9AKK108467A0342
Declaration of Conformity - CE	2CSC444009D2701
KRS Certificate	9AKK108467A0338
LR Certificate	9AKK108467A0332
RINA Certificate	9AKK107992A0866
UL Certificate	9AKK107992A1040
Certification Agency	BV, Korean register, CCC, EAC, UL

Installation

Instructions and Manuals	No document needed

Popular Downloads

Data Sheet, Technical Information	2CSC444002B0204

Classifications

ETIM 8	EC002705 - Holder for cylindrical fuse
ETIM 9	EC002705 - Holder for cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361050
UNSPSC	39121624
eClass	V11.0 : 27142121
IDEA Granular Category Code (IGCC)	4974 >> Holder for cylindrical fuse
Object Classification Code	F

Accessories

© 2024 ABB. All rights reserved.

Identifier	Description	Type	Quantity	Unit Of Measure
2CSM277523R1801	Fuse link	E 9F14 GG2	1	piece
2CSM277303R1801	Fuse link	E 9F14 GG4	1	piece
2CSM277083R1801	Fuse link	E 9F14 GG6	1	piece
2CSM291003R1801	Fuse link	E 9F14 GG8	1	piece
2CSM290983R1801	Fuse link	E 9F14 GG10	1	piece
2CSM290963R1801	Fuse link	E 9F14 GG12	1	piece
2CSM258783R1801	Fuse link	E 9F14 GG16	1	piece
2CSM257603R1801	Fuse link	E 9F14 GG20	1	piece
2CSM256423R1801	Fuse link	E 9F14 GG25	1	piece
2CSM258693R1801	Fuse link	E 9F14 GG32	1	piece
2CSM257513R1801	Fuse link	E 9F14 GG40	1	piece
2CSM256333R1801	Fuse link	E 9F14 GG50	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical Fuse Holders and Fuse Switch Disconnectors






360°

© 2024 ABB. All rights reserved.