Date: 11/04/2023

TR75 Resistance Themometer DiwiTherm®, with

TR75 Resistance Themometer DiwiTherm®, with

Item number:	48727987	
Quantity:	1 pcs.	
Order code:	TR75-1-ZZZ-M-F-C-ZBF-ZZZ-R02000-DR-00150-Z-ZZ	ZZZ00000150AN
Overview:	TR75 Resistance Themometer DiwiTherm®, with digital Display Specifications according to data sheet: TE 60.75 Power supply: Battery powered Unit of measure: Metric (mm) Temperature range: -40...+199,9 °C Instrument version: Axial, panel mounting Fitting style: Compression fitting with stainless steel ferrule Thread size: G 1/2 B Lead wire insulation: Silicon jacket, shielded, application range -40...+180 °C W-Dimension: 2000 mm Sensor diameter: 6.0 mm Sheath material: Stainless steel 316 Ti (1.4571) A-Dimension: 150 mm	
Details:	TR75 Resistance Themometer DiwiTherm®, with digital Display Specifications according to data sheet: TE 60.75 Power supply: Battery powered Unit of measure: Metric (mm) Temperature range: -40...+199,9 °C Instrument version: Axial, panel mounting Fitting style: Compression fitting with stainless steel ferrule Thread size: G 1/2 B Lead wire insulation: Silicon jacket, shielded, application range -40...+180 °C W-Dimension: 2000 mm Sensor diameter: 6.0 mm Sheath material: Stainless steel 316 Ti (1.4571) A-Dimension: 150 mm	

© 2023 - WIKA Instruments s.a.r.l.