Date: 13/04/2023

RLT-1000; Guide tube length: 290.0 ; 4...20 mA

RLT-1000; Guide tube length: 290.0 ; 4...20 mA

Item number: 48735115

Quantity: 1 pcs.

Order code: RLT-1000-2-1CZ-8M-M02900004002-4-Z3 Z1W101ARL1ZL1

Overview:
RLT-1000; Guide tube length: 290.0 ; 4...20 mA
Level sensor, Stainless steel version Model RLT-1000
Output Signal: 4...20 mA
Power supply: 12 … 32 V DC
Process connection: G 1, installation from outside
Electrical connection: Angular connector DIN 175301-803 A, IP65
pin assignment el. connection: UB=1, 0V=2
Guide tube length: 290.0 mm
100% level (X): 40,0 mm
Accuracy / Resolution: 10 mm
Wetted parts: Stainless steel 1.4571
medium temperature: -30 °C ... 80 °C
Float: Cylindrical float Ø 30 mm, 1.4571, PN10
Specifications according to data sheet: LM 50.02

Details:
RLT-1000; Guide tube length: 290.0 ; 4...20 mA
Level sensor, Stainless steel version Model RLT-1000
Output Signal: 4...20 mA
Power supply: 12 … 32 V DC
Process connection: G 1, installation from outside
Electrical connection: Angular connector DIN 175301-803 A, IP65
pin assignment el. connection: UB=1, 0V=2
Guide tube length: 290.0 mm
100% level (X): 40,0 mm
Accuracy / Resolution: 10 mm
Wetted parts: Stainless steel 1.4571
medium temperature: -30 °C ... 80 °C
Float: Cylindrical float Ø 30 mm, 1.4571, PN10
Specifications according to data sheet: LM 50.02

© 2023 - WIKA Instruments s.a.r.l.