Specifications

Eaton 193161



Catalog Number: 193161

Eaton xEnergy Basic EWK small distribution board. Wall-mounted enclosure EWK complete, IP31, 72 SU, protection class II, HxWxD=500x550x230mm

General specifications

Product Name
Eaton xEnergy Basic EWK small distribution board

Catalog Number
193161

EAN
9010238007444

Product Length/Depth
230 mm

Product Height
500 mm

Product Width
550 mm

Product Weight
14.2 kg

Compliances
RoHS conform

Certifications
IEC/EN 62208

Powering Business Worldwide

Product specifications

Special features

IP31 Protection Class II Steel sheet enclosure white (RAL 9016)

Type

Basic device ECO distribution board Installation distribution board

Features

EMC-version
Earthing terminal block
Neutral terminal block

Fitted with:

Installation panel for modular installation devices
Locking screws can be sealed
Enclosure
Neutral-/protective conductor terminal

Enclosure material

Steel

Built-in height

500 mm

Built-in width

550 mm

Cable entry postion

Cable entries on top and bottom via F3A flange (not part of delivery), back plate

Terminal type

Plug-in terminals

Built-in depth

230 mm

Closure type

Other

Cover/door color

White

Cover/door model

Closed

Cover/door type

Door
Single

RAL-number

Resources

Brochures

eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf

eaton-xenergy-basic-ewk-flyer-fl019004en-en-us.pdf

Catalogs

eaton-xcomfort-compact-distribution-catalog-ca015004en-en-us.pdf

Declarations of conformity

DA-DC-03_EWK-G_31

03_ewk-g_31_220119.pdf

Drawings

eaton-low-voltage-switch-gear-dimensions-1230dim-443.eps

9016

Width in number of modular spacings

24

Ambient operating temperature details

-5 °C - 40 °C

Application

Indoor

Voltage rating at AC

400 V AC

Color

White

Traffic white (RAL 9016)

Number of rows

3

Frequency rating of contacts

50 Hz

Module rack type

Rail frame

Degree of protection

IP31

IK08 (impact resistance)

Number of module space units per row

24

Protection class

II (totally insulated)

Protective shrouding material

Plastic

Functions

Extension possible

Basic device

Material

Polystyren (plastic)

Sheet steel, powder-coated

Mounting method

Surface mounting

DIN-rail

Surface mounted (plaster)

Internal depth

128 mm

PE and N terminal number and cross section

N: 2 x 21 x (0.75 mm² - 4 mm²)

PE: 2 x 6 x (1.5 mm² - 16 mm²)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia