*Date: 11/04/2023*

# TW15-H 1/2NPT 1/2 NPT female U=50 mm B=0.260 inch (6.6 mm) SS316/316L

## Threaded Thermowell TW15, solid machined

| | |
|---|---|
| Item number: | 48630086 |
| Quantity: | 1 pcs. |
| Order code: | TW15-H-A-M-ND-UD-00050-00045-G3-A-0160-0130-ZZ-ZZ00088<br>Z00088IZZZYQ2Z |
| Overview: | TW15-H 1/2NPT 1/2 NPT female U=50 mm B=0.260 inch (6.6 mm) SS316/316L<br>Process thread [P or E]: 1/2NPT<br>Connection to thermometer [N]: 1/2 NPT female<br>Thermowell style: Tapered<br>Head length [H]: 45 mm<br>Insertion length [U]: 50 mm<br>Root diameter [Q]: 16 mm<br>Tip diameter [V or F3]: 13 mm<br>Bore size [B or d1]: 0.260 inch (6.6 mm)<br>Bore depth / stem length (US) [A]: 88 mm<br>Specifications according to data sheet: TW 95.15 |
| Details: | Threaded Thermowell TW15, solid machined<br>Specifications according to data sheet: TW 95.15<br>Head design: Hexagon<br>Thermowell style: Tapered<br>Unit of measure: Metric (mm)<br>Process thread [P or E]: 1/2 NPT<br>Connection to thermometer [N]: 1/2 NPT female<br>Insertion length [U]: 50 mm<br>Head length [H]: 45 mm<br>Material: Stainless steel 316/316L<br>Bore size [B or d1]: 0.260 inch (6.6 mm)<br>Root diameter [Q]: 16 mm<br>Tip diameter [V or F3]: 13 mm<br>Bore depth / stem length (US) [A]: 88 mm<br>Tip thickness [Tt]: 0.250 inch (6.4 mm) |

*© 2023 - WIKA Instruments s.a.r.l.*