Date: 24/04/2023

232.30.063 2 bar 1/4 NPT lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number: 46826739

Quantity: 1 pcs.

Order code: 232.30-C-BG320Z-NB-UZEZCZZ-ZZZZZZZ 313D41ZI3W0 Z2Z-IZZZZZZ121ZZ
LABEL-PG1DE-ZZZZZ

Overview:
232.30.063 2 bar 1/4 NPT lower mount
Measuring System 316 SS
Ingress protection: IP 65
class 1.6
Window: polycarbonate
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Pressure Gauge Standard: International (standard Europe)
stop-pin at zero
WIKA
with Serial number
Label: WIKA standard without / with Tag-number

Details:
Bourdon Tube Pressure Gauges, Safety Pattern
Series EN 837-1
Model: 232.30
Specifications according to data sheet: PM 02.04
Measuring system: stainless steel
Case filling: without
Nominal size: 063 mm
Measuring range: gauge pressure range
Scale range: 0...2 bar
Process connection: 1/4 NPT
Connector location: lower mount
Window: polycarbonate
Pointer: standard pointer
Accuracy class: class 1.6
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: prepared for filling
Ingress protection: IP 65
Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Movement: stainless steel
Packaging: single packing

© 2023 - WIKA Instruments s.a.r.l.

Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
stop pin on dial: at zero
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.