CAT. N° 0 227 00



AUXILIARY CONTACT - FOR ISOLATING SWITCH - N/C + N/O

Pack (number of units)	1
Volume (dm³)	0,211
Weight (g)	52,00

Product characteristics

Accessories

Auxiliary contact

- N/O + N/C

General characteristics

Proximity switching from 16 to 80 A

- Safety switch for disconnection and isolation of phases
- IP 2X
- Double breaking on each phase
- Red rotary handle on yellow plate
- Immediate display of position
  - horizontal: open (O)
  - vertical: closed (I)
- Equipped with non reversible terminals
- Conform to IEC EN 60947-3
- UL-cUL (USA and Canada) agreements (except boxes)
- IP 65 - IK 07 for boxes

Documentation

Catalogue pages & additional information

- Description page (p.176)
- Isolator switches

Agreements & certificates of conformity

- UL listed cULus-NLRV-E57817
- UL listed cUL-NLRV7-E57817

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.