Date: 23/01/2024

A52.160/1, 0...120°C, 100x8mm

Bimetal Thermometer, Industrial Series

Item number:	3904393
Quantity:	1 pcs.
Order code:	A52.160-1-C1F-BS-C100GZZ-Z-ZZZ TD FZZVC-AZ1ZZZZZZZZZZ
Overview:	A52.160/1, 0...120°C, 100x8mm Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting) flat instrument glass *WIKA*
Details:	Bimetal Thermometer, Industrial Series Specifications according to data sheet: TM 52.01 Accuracy class: class 1 per EN 13190 Case: stainless steel Stem material: stainless steel Model: A52.160, nominal size 160, location of stem centre back Connection design: 1, plain stem Scale range: 0 °C ... 120 °C Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting) Stem diameter: 8 mm Insertion length L1: 100 mm norm-mark on dial: *EN 13190* accuracy class on dial: *Cl.1* Bimetallic thermometer, for industrial applications A52L Specifications according to data sheet: TM 52.01 Accuracy class: class 1 per EN 13190 Case: stainless steel Stem material: stainless steel Model: A52.160, nominal size 160, location of stem centre back Connection design: 1, plain stem Scale range: 0 °C ... 120 °C Process connection: plain, with neck to fit thermowell (thermowell necessary for mounting) Stem diameter: 8 mm Insertion length L1: 100 mm Window: flat instrument glass Case: Stainless steel Ingress protection: IP 43 Manufacturer logo: *WIKA* Stem material: stainless steel

© 2024 - WIKA Instruments s.a.r.l.