High degree of protection
Cold impact resistance



Corrosion-resistant

Robust

Reliability

Temperature-resistant

Application range

Equipment group II / Category 2G+1D
Devices, machines and apparatus
For mobile applications in offshore and marine industries
Chemical and petrochemical industry

Design

Metric connection thread acc. to EN 50262

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Approvals:	CE 0637 Ex II 2G Ex eb IIC Ex II 1D Ex ta IIIC IECEx IBE 13.0029X
Material:	Body: nickel-plated brass O-ring: NBR
Protection rating:	IP 68
Temperature range:	-30°C to +90°C

PN 0486/01_03.10
©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

Part number	Article designation / size	SW (mm)	Thread length/ D (mm)	Outer Ø (mm)	PU
SKINDICHT® BL-M ATEX					
52103103	12 x 1,5	16	5.0	17,8	50
52103113	16 x 1,5	20	5.0	22.0	50
52103123	20 x 1,5	24	6.0	26,4	50
52103133	25 x 1,5	29	7.0	31,9	50
52103143	32 x 1,5	36	8.0	39,6	25
52103153	40 x 1,5	45	8.0	49,5	25
52103163	50 x 1,5	54	9.0	59.0	10
52103173	63 x 1,5	67	10.0	73,5	10

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.