Date: 25/04/2023

230.15.2" 250 bar 2nd scale psi ¼” Swivel Female Face Seal, 9/16-18 UNF, gall resistant lower mount

UHP Bourdon Tube Pressure Gauge

Item number:	48761510
Quantity:	1 pcs.
Order code:	230.15-7-BG525P-9F-UZ-R-DA1-ZZ 26 IE41242 DIAL-UAC1ZZZZZZ21-Z0ZDAEZZZZLZZZZZZZZZZ267BG525PU1
Overview:	230.15.2" 250 bar 2nd scale psi ¼” Swivel Female Face Seal, 9/16-18 UNF, gall resistant lower mount +/- 2/1/2% ASME B40.1 Grade A Switch-Type: Single Reed switch (851.3) Set Point Range between 20% and 95% of the full scale Approvals: AEx/Ex ic IIC T6 Gc and FM Class 1 Div. 2 Groups A, B, C, D flying lead Pressure Gauge Standard: US-Standard 2nd scale red * * above WIKA logo *316L Tube and Connection* *GRADE A**WIKA®* *use no oil* (red) Serial number *...*
Details:	UHP Bourdon Tube Pressure Gauge UHP Models: 230.15 - Ultra High Purity, 316L Nominal size: 2" Unit of outer Scale: bar Measuring range: gauge pressure range Scale range: 0...250 bar 2nd Scale or Special Scale: 2nd scale psi Process connection: ¼” Swivel Female Face Seal, 9/16-18 UNF, gall resistant Connector location: lower mount Switch-Type: Single Reed switch (851.3) Set Point Range between 20% and 95% of the full scale Electrical connection: flying lead Accuracy class: +/- 2/1/2% ASME B40.1 Grade A Window: polycarbonate Case: stainless steel electropolished Wetted Parts: Stainless steel 316L System Quality: Extrude hone/electropolished Connection surface finish: Electro polished Gland/Socket < RA10/RA20 µinch Cleaning: Cleaned acc. to SEMI specifications, Nitrogen purged and double bagged Approvals: AEx/Ex ic IIC T6 Gc and FM Class 1 Div. 2 Groups A, B, C, D Pressure Gauge Standard: US-Standard color for 1.scale (outside): black color for 2.scale (inside): red RAL 3020 dial background: White

© 2023 - WIKA Instruments s.a.r.l.

WIKA®
serial number on dial: Serial number *...*
use no oil (red)
* * above WIKA logo
316L Tube and Connection
GRADE A

© 2023 - WIKA Instruments s.a.r.l.