Date: 24/04/2023

232.50.100 -1/+3 bar Diaphragm Seal lower mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number: 48806036

Quantity: 1 pcs.

Order code: DSS1-MF990.27-123X50-DZZZD-C5A65ZA1-3ZAZZZZZ WAZ-Z
LABEL-PG1DE-ZZZZZ- ZZZZZ
232.50-E-BV340Z-CA-UZHZAZZ-AHAZZZZ 213D311IXX0 Z2Z-IZZZZZZ12ZZZ
H990.27-DN0502B2C1-TL-TLZZZZZ Z
CERT31-EG41-BB-AB- - - - - - - - - -

Overview:
232.50.100 -1/+3 bar Diaphragm Seal lower mount
Measuring System 316L Version 1 small volume (for diaphragm seals)
Ingress protection: IP 65
Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
class 1.0
Window: laminated safety glass
adjustable pointer
Pressure Gauge Standard: International (standard Europe)
WIKA
with Serial number

Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 2 Silicone oil for general applications
Process temperature min.: - 10°C
Process temperature max.: + 100°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C

Diaphragm seal, flange type, flush diaphragm
Model 990.27 DN 50 PN 16 following EN 1092-1
Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603
Sealing face: form B2
Sealing face material: Tantalum; UNS R05200
Diaphragm material: Tantalum; UNS R05200

Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German
Certificate for: Diaphragm seal system with pressure measuring instrument
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis

© 2023 - WIKA Instruments s.a.r.l.

Accuracy: Calibration values listed

Label: WIKA standard without / with Tag-number

Details:

Bourdon Tube Pressure Gauges, Stainless Steel
Series
Model: 232.50
Specifications according to data sheet: PM 02.02
Measuring system: stainless steel
Case filling: without
Nominal size: 100 mm
Scale range: -1...+3 bar
Process connection: Diaphragm Seal
Connector location: lower mount
Window: laminated safety glass
Pointer: adjustable pointer
Explosion protection: ATEX
Ignition protection type: Ex h
Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)
Accuracy class: class 1.0
Overpressure safe: standard
Case material: Stainless steel 1.4301
Case surface: bare
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Special measuring element: Version 1 small volume (for diaphragm seals)
Ingress protection: IP 65
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
with Serial number
Diaphragm seal system with 1 diaphragm seal
Assembly specification High-Side: Direct assembly
System fill fluid: KN 2 Silicone oil for general applications
Process temperature min.: - 10°C
Process temperature max.: + 100°C
Ambient temperature pressure meas. min: + 10°C
Ambient temperature pressure meas. max: + 40°C
Diaphragm seal, flange type, flush diaphragm
Specifications according to data sheet: DS 99.27
Diaphragm seal: Model 990.27
Diaphragm seal: Model 990.27
Process connection standard: following EN 1092-1
Process connection: DN 50
Nominal pressure rating: PN 16

© 2023 - WIKA Instruments s.a.r.l.

Sealing face: form B2
Upper body material / main body material: Stainless steel 1.4404 (316L); UNS S31603
Diaphragm material: Tantalum; UNS R05200
Sealing face material: Tantalum; UNS R05200
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German
Certificate for: Diaphragm seal system with pressure measuring instrument
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis
Accuracy: Calibration values listed

Label: WIKA standard without / with Tag-number

© 2023 - WIKA Instruments s.a.r.l.