*Date: 22/04/2024*

# PCS2PA 80 … 400 bar 1/4 NPT-F, 1/2 -14 NPT-F

## Compact Pressure Switch

Item number: 14147731

Quantity: 1 pcs.

Order code: PCS2PA-BALB-1ASZZZZZZ ZCKW

Overview:

PCS2PA 80 … 400 bar 1/4 NPT-F, 1/2 -14 NPT-F
Compact Pressure Switch
PCS
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
Setting range, working range, proof pressure: 80 … 400 bar, working range 0 … 600 bar, proof pressure 600 bar
Set point definition: Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case

Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range

Details:

Compact Pressure Switch
Model PCS
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Piston Stainless Steel 316, O-Ring FPM
1xSPDT, silver contact
80 … 400 bar, working range 0 … 600 bar, proof pressure 600 bar
Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: without
Switch standard: without
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCS2PA 80 … 400 bar

*© 2024 - WIKA Instruments s.a.r.l.*