CAT. N° 4 160 81



3-POLE CONTACTORS CTX³ 22 - 9 A - 24 V= - 1 NO + 1 NC - SCREW TERMINALS

Pack (number of units)	1
Volume (dm³)	0,431
Weight (g)	479,00

Product characteristics

CTX³ 22
- With integrated auxiliary contacts
- Power terminals: screw terminals

9 A (AC3) - 25 A (AC1)
- Screw terminals
- 3-phase motor 400/415 V : 4 kW
- Control Voltage : 24 V=
- Integrated auxiliary contacts : 1 NO + 1 NC

General characteristics

3-pole contactors CTX³ - 9 A to 100 A industrial contactors
- Conform to IEC 60947-1, IEC 60947-4-1
- Can be equipped with RTX³ thermal relays add-on auxiliary contact blocks, time delay blocks, capacitor switching units and CTX³ interlocking

Documentation

Catalogue pages & additional information
- Technical page (p.186-187)
- Description page (p.190)
- Technical page (p.196-197)
- 3-pole contactors CTX³

Installation & technical data
- F01989EN-06

Installation instructions & related documents
- LE07229AB

Environmental product profile
- LGRP-00209-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.