Rittal – The System.

Faster – better – everywhere.

Wire end ferrule Loose – AS 4050.774

Date : Oct 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Wire end ferrule Loose – AS 4050.774

created: 26.10.2021 build on www.rittal.com/us-en



Product description

Description:	With plastic collar.
Technical specifications:	Heat resistant up to 105 °C
Standards:	AEH DIN 46228
Material:	E-Cu, tin-plated Plastic collar: Polypropylene
Note:	UL-certified in conjunction with the relevant tools, e.g. crimping machines.

Product description

For cross section:	1.5 mm²
AWG:	16
Length:	10 mm
Internal diameter:	3.5 mm (0.14 ")
Version:	for manual wire processing and crimping machines 0.5 - 2.5 mm² (length 8 mm)
Color:	Red
Color code:	Rittal color code: yes

For:	Manual assembly
Delivery form:	Loose
Packaging unit:	500 pc(s).
Weight/packaging unit:	0.5 kg (1.1 lb.)
Copper weight (kg per piece):	0
EAN:	4028177815711
Customs tariff number:	85369010
ETIM 7.0:	EC000005
ETIM 6.0:	EC000005
eCl@ss 8.0/8.1:	36659290
eCl@ss 6.0/6.1:	36659290
Product description:	Wire end ferrules for crimping machines and manual preassembly, 1.5 mm², AWG 16, 10 mm, red, loosely packed, 500 pc(s).

Approvals

Approvals:	UL + C-UL UR