# STFM360

## Suretime Flush Mount 360 Degree PIR



### Features & Benefits

- Flush mount PIR sensor suited for a wide array of indoor applications
- Manual override (Pulse) for extended light on times
- Adjustable time ON setting
- Adjustable lux level
- 60mm diameter ceiling cut out

### Technical Data

| | |
|---|---|
| **Operating Voltage** | 230V AC |
| **Frequency** | 50Hz |
| **Installation Type** | Flush Mount |
| **Earth Class Rating** | Class II |
| **Operating Temperature** | -20°C to 40°C |
| **Ingress Protection Rating** | IP44 |
| **Setting Type** | Dial |
| **Approved Mounting Height (m)** | 3 |
| **Motion Detection (m)** | 6 Diameter |
| **Detection Angle** | 360° |
| **Hole Cut-Out Size (mm)** | 60 |
| **Standby Consumption** | <1W |
| **Number of Channels** | 1 |

Data sheet
# STFM360

Light / PIR Presence Detectors

| | |
|---|---|
| **Switch rating** | 200W LED, 1000W Halogen, 200W Fluorescent/Low Energy Lighting |
| **ON Time Adjustment** | 3 Seconds to 18 Minutes. User Adjustable |
| **Lux Level** | 10 to 1000 |
| **Detection Range (M)** | 6 Diameter |
| **Permanent ON Facility** | Yes (Pulse Override) |
| **Dusk Till Dawn** | No |
| **Multiple Unit Support** | Up to 5 Units In Parallel |
| **Cable Entry(s)** | Back Entry |

## General

| | |
|---|---|
| **Weight (g)** | 86 |
| **Height (mm)** | 76.5 |
| **Width (mm)** | 82 |
| **Depth (mm)** | 82 |
| **Body Construction** | Polycarbonate |
| **Product Colour** | White |
| **Accessories (Included)** | Cover Cover, Screws |
| **EAN Number** | 5012483014288 |
| **Guarantee Period** | 2 Years |
| **Trade Tariff Commodity Code** | 8536508090 |

Data sheet
**STFM360**

Light / PIR Presence Detectors

## Line Diagrams

