Date: 11/04/2023

TG54.063/4, DS, 0...100°C , L1=100 mmx8mm

Model: TG54.063

Item number:	48759908
Quantity:	1 pcs.
Order code:	TG54.063DS-4-C1EZ-ND-C0100H1-ZAHAZZZ TO F-2ID-AZ1ZZZZZ2ZZZZ
Overview:	TG54.063/4, DS, 0...100°C , L1=100 mmx8mm Process connection: 1/2 NPT laminated safety glass liquid damping Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Stem material: 316SS Ingress protection: IP 65 Permissible ambient temperature: -40 ... +70 °C *WIKA* with Serial number
Details:	Model: TG54.063 Specifications according to data sheet: TM 54.02 Accuracy class: class 1 per EN 13190 Nominal size: 063 Connection location: back mount, adjustable Connection design: 4, compression fitting, sliding on stem Process connection: 1/2 NPT Scale range: 0 °C ... 100 °C Stem diameter: 8 mm Insertion length L1: 100 mm Window: laminated safety glass Damping: liquid damping Stem material: 316SS Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Ingress protection: IP 65 Permissible ambient temperature: -40 ... +70 °C with Serial number Manufacturer logo: *WIKA*

© 2023 - WIKA Instruments s.a.r.l.