CM.BP21PB – 21 Piece General Maintenance Kit



Content:

- 160mm Side Cutting Pliers 192.16G
- 250mm Multi-grip Pliers 170A.25
- 6 Screwdrivers:
  - 4 x Slotted: 3.5x75- 4x100 - 5.5x100 – 6.5x150mm
  - 2 x Pozidriv: 1x100 – 2x125 mm
- Hacksaw Frame - 601 + Blade
- 3M Metric Measuring Tape - 893A.319
- Adjustable Spanner 8'' – 113A.8C
- Adjustable Spanner 12'' – 113A.12C
- Set of 9 long hex head keys 83SH.JP9A –
  - 1.5- 2- 2.5- 3- 4- 5- 6- 8- 10 mm
- Toolbox PRO BOX 20" - 51cm - BP.P20

Features;

192.16G Side Cutters –

- Cutting edges designed to cleanly cut all types of wire: piano wire, soft wires and modern materials (max. 200 kg/mm).
- High durability Chrome-Molybdenum-Vanadium steel, very hard cutting edges 61/63 HRc.
- 160mm Length

170A.25 Multi-Grip Plier

- Ergonomic handle for comfortable use
- Self-gripping teeth
- 250mm Length
- Technical Conformity - NF ISO 8976 - ISO 8976 - DIN ISO 8976 - ASME B107.500

Protwist Slotted PL Screwdrivers.

- Polyamide core for high resistance to impact, stress, abrasion & chemical agents.
- Carbon Silicium (Silicon Carbon) blades - extreme strength and resistance to bending.
- Hardened black blade tip.
- 3.5mm wide x 75mm long, 4mm wide x 100mm long, 5.5mm x 100mm long, 6mm x 150mm
- Technical Conformity - NF ISO 2380-1, NF ISO 2380-2, ISO 2380-1, ISO 2380-2, DIN ISO 2380-1, DIN ISO 2380-2, ASME B107.600

Protwist Pozidriv Screwdrivers.

- Polyamide core for high resistance to impact, stress, abrasion & chemical agents.

- Carbon Silicium (Silicon Carbon) blades - extreme strength and resistance to bending.
- Hardened black blade tip.
- Technical Conformity - NF ISO 8764-1, NF ISO 8764-2, ISO 8764-1, ISO 8764-2, DIN ISO 8764-1, DIN ISO 8764-2, ASME B107.600

601 Hacksaw

- Blade tension 80 kg.
- 2 blade positions: 45° and 90°.
- Takes 300 mm blade.
- Technical Conformity - NF E 73-073, DIN 6473

893A.316 3M tape measure

- Ergonomic, ABS material.
- Tape with mat anti-reflection nylon tape.
- 3m Metric only tape measure
- Class II accuracy

113A.8C and 113A.12C Adjustable wrenches

- Non-protruding moving jaw at maximum capacity.
- Presentation: chromed body and polished head faces
- 113A.8C – 8” Long / 27mm Jaw
- 113A.12C – 12” Long / 34mm Jaw
- Technical conformity - NF ISO 6787, ISO 6787, DIN 3117, ASME B107.100

83SH.JP9A Ball end hex key set in wallet

- Contains: 1.5, 2, 2.5, 3, 4, 5, 6, 8 & 10mm.
- Manufactured in silicon steel.
- The spherical head allows to handle screws with a tilt angle up to 30°.
- Finish: phosphate-coated.
- Technical Conformity - NF ISO 2936, ISO 2936, DIN ISO 2936, ASME B18.3.2M

BP.P20 Plastic toolbox – 20” / 508mm

- Reinforced polypropylene construction
- Metal wire hinges
- Storage capacity: 36 litres.
- External measurements 508 x 268 x 273 mm (L x W x H)