Date: 11/04/2023

F73.160/2, 0...100°C, L1=80 mmx12mm,

Gas actuated thermometer, stainless steel series

Item number:	48788680
Quantity:	1 pcs.
Order code:	F73.160-C1E-2GD-G0080-S05-1-Z-HZZ-ZZZZZZ G8 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ
Overview:	F73.160/2, 0...100°C, L1=80 mmx12mm, G 1/2 B radial bottom Surface mounting flange, stainless steel stainless steel armoured capillary Capillary length: 5 m laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.160, nominal size 160, with capillary Unit: °C Scale range: 0 °C ... 100 °C Connection design: 2, male nut Process connection: G 1/2 B Stem diameter: 12 mm Insertion length L1: 80 mm Capillary: stainless steel armoured capillary Capillary length: 5 m Design of case mounting: Surface mounting flange, stainless steel Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: radial bottom Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.