Specifications

Eaton 102445



Catalog Number: 102445

Eaton xEnergy Basic LV systems Low voltage switchgear. Metal door, for HxW=1760x600mm, white

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	102445
EAN	**Product Length/Depth**
4015081023332	45 mm
Product Height	**Product Width**
1710 mm	615 mm
Product Weight	**Compliances**
9 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory
Floor-standing enclosure
Service distribution board IVS
Accessory consideration

Special features

Can be used as left door for two-leaf versions
Closed
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock
Left door for two-section design with 1200 mm enclosure widths

Type

Additional equipment for floor-standing service distribution board IVS

Features

EMC-version

Accessory/spare part type

Doors

Surface finishing

With powder coating
Powder coating

Color

White
Traffic white (RAL 9016)

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

1760 mm

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_Z-DS

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Suitable for width

600 mm

Cover/door type

Three-point turn-lock

Material

Steel

Sheet steel

Housing material

Sheet steel

Model

Stop door

Mounting method

Floor standing distribution board

Flush mounting

Surface mounting

Functions

Floor-standing enclosure

Additional equipment

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia