Specifications

Eaton 20NHG0B

Catalog Number: 20NHG0B

Eaton Bussmann series low voltage NH Fuse, 500V, 20A, Combination fuse status indicator, fuse, Class C gL/gG

General specifications

Product Name
Eaton Bussmann series low voltage NH Fuse

Catalog Number
20NHG0B

EAN
5027590468190

UPC
051712232623

Product Length/Depth
125 mm

Product Height
58 mm

Product Width
30 mm

Product Weight
299.3333333 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269-1
IEC 60269-2
DIN 43620

Product specifications

Type

fuse

Application

industrial

Utilities, Solar, Wind

Amperage Rating

20 A

Fitted with:

Metal gripping lugs

Fuse size

NH0

Current type

AC

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Connection

Blade end

Construction

NH0

Resources

Catalogs

CA134002EN

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

NH Fuse links, bases and gear

Declarations of conformity

CE NH Size 0, 500V fuse-links

UKCA NH Size 0, 500V fuse-links

Multimedia

Eaton Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

10164 NH 500 Volts gG

Construction size

NH0

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

EBF Vertical fuse rail

EBV Vertical fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

500 V

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia