www.flex-tools.com

this is proformance FLEX

FHE 2-22 SDS-plus

Rotary hammer drill, 2,3 kg, SDS-plus

Order no. 413674

GTIN 4030293177147



- Light-weight and handy 710 watt pistol-shaped fixing hammer
- Hammer drilling
- Max.drilling range up to 22 mm in concrete
- Ideally suited for drilling/hammer drilling, diameter 4-12 mm in concrete for attachment of dowels and anchors
- Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- Depth limit gauge: for precision drilling
- Accelerator switch with lock-on function
- Robust glass fibre reinforced housing

Tool-Free

L-BOXX

Technical data

Power consumption	710 W
Voltage	230 V
Frequency	50/60 Hz
Tool holder, drill and chisel	SDS-plus
Max. single impact energy	2.1 J
No-load speed	0 - 1400 rpm
No-load blows	0 - 4300 1 rpm
Max. drilling diameter in concrete	22 mm
Max. drilling diameter in wood	26 mm
Max. drilling diameter in steel	13 mm
Cable length	4.0 m
Dimensions WxLxH	345 x 80 x 200 mm
Weight	2.3 kg

Standard equipment

1 Side handle (416126)
1 Depth stop (416118)
1 Carrying case L-BOXX® (414085)
1 Case insert (414042)