TRICOGREEN®

new



25 | 20 bar

+60 / - 15 °C

1. Yellow PVC covering with two green bands
2. Intermediate layer of PVC
3. Textile knitted reinforcement TNT
4. Intermediate layer of soft black PVC
5. Smooth black inner tube

APPLICATIONS

Watering, irrigation, water supply and delivery.

MARKING TRICOGREEN 80% recyclé Soft & Flex Tricoflex Non Torsion Ø int [WP/BP] BAR REACH-Compliant [Batch number] TRICOFLEX

Flexible multilayer hose.

Exterior covering in ultra UV-resistant PVC. With woven polyester fibre reinforcement and two-layer smooth lining.

ADVANTAGES

Crafted with 80% recycled PVC, TRICOGREEN® combines exceptional quality, environmental responsibility, and high performance. Its innovative design ensures outstanding resistance to impact and crushing, delivering long-lasting durability.
With its knitted TNT reinforcement, TRICOGREEN® resists twisting under water pressure, guaranteeing smooth and efficient watering. Its flexibility and robustness make it both easy to handle and highly reliable for everyday use.
LNE-certified, TRICOGREEN® is the responsible choice for those who demand premium quality without compromise.

CONNECTORS

Connectors with band, screw or 'O' type clamps.
Automatic connectors for watering.

CHEMICAL RESISTANCE

See table pages 110 to 113 column A.



TRICOGREEN® offers a sustainable alternative, delivering performance equivalent to TRICOFLEX® while **reducing greenhouse gas emissions by an estimated 50%**.

Lightweight and easy to handle

ANTI-UV
UV resistance

mm	mm	mm	bar	bar	mm	Yellow		
						25 m	50 m	100 m
12,5	**17,6**	2,55	25	10	125	110080	110081	110082
15	**20,5**	2,75	25	10	135	110093	110094	110095
19	**25,3**	3,15	23	9	180	110100	110101	110102
25	**32,3**	3,65	20	8	240	110123	110124	110125

Crush resistance

Anti-twist knitting (Tricoflex Non Torsion)

*National metrology and testing laboratory. https://www.lne.fr/en