Technical sheet

ALL SEASON

Description :

The ALL-SEASON Surflex® safety cap with its ABS protective shell is an essential model for all professionals working outdoors and/or indoors. It protects against impacts and provides adequate ventilation to the head. Comfort is maximized by the use of a double elastic located under the occipital bone. The visor is a standard size of 5cm without compromising the field of vision.



THE ALL-SEASON ANTI-BUMP CAP STANDARDIZED EN 812: THE VERSATILE

Head protection with ABS shell standardized **EN 812: 2012**

Side vents and anti-sweat absorbent band inside

Reflective strips



5 cm visor

Elastic support adjustable to keep the cap on the head in all circumstances.



Ventilated shell Optimization of head ventilation to maximize comfort

SURFLEX®

SURFLEX®

Technical characteristics

ALL SEASON

REFERENCES

Gray	ALLC03V05
Blanc	ALLC00V05
Jaune HV	ALLC05V05
Green	ALLC08V05
Navy blue	ALLC02V05
Orange HV	ALLC06V05
Noir	ALLC01V05
Rouge	ALLC07V05
Royal blue	ALLC10V05
Navy blue / Orange	ALLC26V05
Navy blue / Yellow	ALLC25V05
Beige	ALLC04V05



GROSS WEIGHT

+/- 170 Grammes

SIZE

Single adjustable (56 cm - 64 cm)

MATTER

0% Metal

Shell: ABS (Acrylonitrile butadiene styrene)

Fabric: 100% Polyester (Origin: China)

INTERVIEW

Wash at 30°C I Do not bleach I Do not tumble dry I Do not iron I Do not dry clean I Professional washing excluded



CARDBOARD DIMENSIONS

Box of 50 pieces

L 60 cm x l 40 cm x h 40 cm | Poids : 9 kg

Customs code: 65061000

LIFETIME

3 years *from the date of manufacture: month / year of production indicated on the shell in the form of a clock.*

COMPLIANCE

Standard EN 812: 2012

- *EU type examination certificate issued by ALIENOR CERTIFICATION. Notified body No. 2754. (Download compliance documents)*

Complies with Regulation (EU) 2016/425 relating to Personal Protective Equipment (PPE) Cat II.

Please note: The safety cap does not replace the construction helmet.

MARKING

Frontal



Embroidery | Transfert
↔ 85 mm x ↕ 45 mm Max

Sides



Transfert ↔ 60 MM X ↕ 20 MM Max

Learn more at www.surflex.eu