Date: 11/04/2023

S73.100/4, -200...+50°C, L1=445x6mm,

Gas actuated thermometer, stainless steel series

Item number: 48782079

Quantity: 1 pcs.

Order code: S73.100-CNA-4ND-B0445-ZZZ-Z-Z-HZZ-ZZZ1ZZ G5 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
CERT31-EF2T-AI- - - - - - - - - - -

Overview:
S73.100/4, -200...+50°C, L1=445x6mm,
1/2 NPT axial
laminated safety glass
class 1 per EN 13190
WIKA
with Serial number
Inspection certificate 3.1 per EN 10204
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and French
Certificate for: thermometer mechanical
Accuracy: Calibration values listed, 3 test points

Details:
Gas actuated thermometer, stainless steel series
Specifications according to data sheet: TM 73.01
Case: stainless steel
Stem material: stainless steel
Model: S73.100, nominal size 100, adjustable stem and dial
Unit: °C
Scale range: -200 °C ... +50 °C
Connection design: 4, compression fitting, sliding on stem
Process connection: 1/2 NPT
Stem diameter: 6 mm
Insertion length L1: 445
Ignition protection type: without
Zone: without
Accuracy class: class 1 per EN 13190
Ingress protection: IP 65
Window: laminated safety glass
Case: Stainless steel
Connector location: axial
Manufacturer logo: *WIKA*
Permissible ambient temperature: -40 … +60 °C
with Serial number
Inspection certificate 3.1 per EN 10204
Certificate type: Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and French
Certificate for: thermometer mechanical

© 2023 - WIKA Instruments s.a.r.l.

Accuracy: Calibration values listed, 3 test points

© 2023 - WIKA Instruments s.a.r.l.