Date: 11/04/2023

MAGXXDN - 10...250 bar - 1/4 NPT-F - 1/2 -14 NPT-F

Diaphragm pressure switch

Item number: 48785673

Quantity: 1 pcs.

Order code: MAGXXDN-BBSSB-1AMZZZZ1ZZZZZZZZZZZZZZZZZZZ ZCK5DW
F4-C5- - - - -

Overview:
MAGXXDN - 10...250 bar - 1/4 NPT-F - 1/2 -14 NPT-F
Diaphragm pressure switch
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 2 x SPDT or 1 x DPDT silver contact
setting range: 10...250 bar
Standard, working range = 0...250 bar, proof pressure 400 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Hastelloy C 276//Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point not defined
Approvals / Certificates
IECEx-ATEX Ex d

Details:
Diaphragm pressure switch
Flameproof enclosure Ex d
Model MA
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span
Contact version: 2 x SPDT or 1 x DPDT silver contact
setting range: 10...250 bar
working range: Standard, working range = 0...250 bar, proof pressure 400 bar
Set Point not defined
Unit: bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
MAGXXDN
Diaphragm: Hastelloy C 276//Connection: Stainless steel AISI 316L

© 2023 - WIKA Instruments s.a.r.l.

Date: 11/04/2023

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.