DATASHEET - M22S-DH-W-X1

Pushbutton, RMQ-Titan, Extended, momentary, White, inscribed, Bezel: black

Part no. **M22S-DH-W-X1**
216662

Product name	Eaton Moeller® series M22 Pushbutton
Part no.	M22S-DH-W-X1
EAN	4015082166625
Product Length/Depth	30 millimetre
Product height	35 millimetre
Product width	30 millimetre
Product weight	0.012 kilogram
Certifications	IEC/EN 60947-5 UL File No.: E29184 CSA-C22.2 No. 94-91 CSA CSA-C22.2 No. 14-05 UL 508 UL Category Control No.: NKCR CSA Class No.: 3211-03 UL IEC/EN 60947 CE CSA File No.: 012528 VDE 0660 DNV GL LR
Product Tradename	M22
Product Type	Pushbutton
Product Sub Type	None
Bezel color	Black
Bezel material	Plastic
Design	Extended Classical
Features	Labelled
Fitted with:	Front ring
Inscription	Inscribed
Degree of protection	NEMA 3R IP66 NEMA 4X IP67 NEMA 12 IP69K NEMA 13
Degree of protection (front side)	IP67/IP69K NEMA 4X
Lifespan, mechanical	5,000,000 Operations
Opening diameter	22.5 mm
Operating frequency	3600 Operations/h
Product category	RMQ-Titan
Size	Front dimensions: 22 x 22 mm
Type	Pushbutton actuator
Mounting position	As required
Shock resistance	30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Connection to SmartWire-DT		Yes With SWD-RMQ connections
Actuating force		5 N
Actuator color		White
Actuator function		Momentary Spring-return
Force for positive opening - min		0 N
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])

Colour button		White
Number of command positions		1
Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
Type of button		High
Suitable for illumination		No
With protective cover		No

Labelled	Yes
Switching function latching	No
Spring-return	Yes
With front ring	Yes
Material front ring	Plastic
Colour front ring	Black
Degree of protection (IP), front side	IP67/IP69K
Degree of protection (NEMA), front side	4X

© 04/2023 by Eaton Industries GmbH