Date: 11/04/2023

ABRPP1,5"-PPOO-L1,010/16-PP55A

ABRPP1,5"-PPOO-L1,010/16-PP55A

Item number: 48787673

Quantity: 1 pcs.

Order code: FLSPCMNZ1030MM2ZZGEZZ0100O0950OZZZZZZZZZZNZZ
KGOAA10102ZZ

Overview: ABRPP1,5"-PPOO-L1,010/16-PP55A
Float Switch Type FLS-PA
Pressure: max. 3 bar
Temperature range: -10°C up to 80°C
Fluid density: 1030 kg/m³
Material: Polypropylene (PP)
Housing: Polypropylene (PP)
Ingress protection: IP65
Electrical connection: M20 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 1-1/2"BSP
Switch function 1: Opening on rising level (SPST) 100 mm
Switch function 2: Opening on rising level (SPST) 950 mm
Switch rating: max. AC 230V; 100VA; 1A / DC 230V; 50W; 0.5A
Float: Polypropylene PP55A; Float outer diameter: 55 mm
Number of floats: 2 pcs
Guide tube: OD 16 mm Insertion length (L): 1010 mm

Float can't be mounted through the connection nozzle

Details: ABRPP1,5"-PPOO-L1,010/16-PP55A
Float Switch Type FLS-PA
Pressure: max. 3 bar
Temperature range: -10°C up to 80°C
Fluid density: 1030 kg/m³
Material: Polypropylene (PP)
Housing: Polypropylene (PP)
Ingress protection: IP65
Electrical connection: M20 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 1-1/2"BSP
Switch function 1: Opening on rising level (SPST) 100 mm
Switch function 2: Opening on rising level (SPST) 950 mm
Switch rating: max. AC 230V; 100VA; 1A / DC 230V; 50W; 0.5A
Float: Polypropylene PP55A; Float outer diameter: 55 mm
Number of floats: 2 pcs
Guide tube: OD 16 mm Insertion length (L): 1010 mm

Float can't be mounted through the connection nozzle

© 2023 - WIKA Instruments s.a.r.l.