# DATASHEET - 2P 10X38MFH 30A 600V CLASS CC-INDICATOR



**Fuse holder, low voltage, 30 A, AC 600 V, 10 x 38 mm, CC, 2P, UL, with indicator**

**Part no.** 2P 10X38MFH 30A 600V Class CC-indicator
**Catalog No.** CHCC2DIU

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse accessory |
| Basic function | | | Fuse-holder |
| Field of application | | | low voltage |
| Rated current | I | A | 30 |
| Rated voltage | | | AC 600 V |
| Size | | | 10 x 38 mm |
| Utilization category | | | CC |
| Status indicator | | | with indicator |
| Description | | | DIN rail mounting<br>colour-coded<br>Rated for use with 75°C or 90°C wire<br>fine stranded wire<br>spade terminals and with comb-bus bars<br>Use any higher temperature rated wire with appropriate derating.<br>Modular |
| Number of poles | | | 2P |
| usable for size/applications | | | for cylindrical fuse-links |
| Standard/Approval | | | UL |
| Standards/Regulations | | | IEC<br>cULus<br>CCC<br>CSA<br>UR |

## Technical data ETIM 7.0

| | | | |
|---|---|---|---|
| Circuit breakers and fuses (EG000020) / Holder for cylindrical fuse (EC002705) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Holder for cylindrical fuse (ecl@ss10.0.1-27-14-21-21 [ADI305007]) | | | |
| Nominal voltage | | V | 600 |
| Mounting method | | | DIN rail |
| For fuse size | | | 10x38 mm |
| Number of poles | | | 2 |
| Concurrently switching N-neutral | | | No |
| Lockable | | | Yes |
| Optical defect indication | | | Yes |
| Width in number of modular spacings | | | 2 |
| Built-in depth | | mm | 45.1 |
| Degree of protection (IP) | | | Other |


© 02/2021 by Eaton Industries GmbH