DATASHEET - Z-BB/UL18/1P1MU/57

Phase busbar, 1-phase, 18qmm, pin, 1m

Part no. **Z-BB/UL18/1P1MU/57**
171128

General specifications

Product name	Eaton Moeller series busbar
Part no.	Z-BB/UL18/1P1MU/57
EAN	4015081676187
Product Length/Depth	1009.8 millimetre
Product height	56.8 millimetre
Product width	19.3 millimetre
Product weight	0.74 kilogram
Compliances	RoHS conform
Product Tradename	None
Product Type	Busbar
Product Sub Type	None

Product Specification Details

Accessory/spare part type	Busbar for miniature circuit breaker
Ambient operating temperature - max	100 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for industrial and advanced commercial applications
Color	Other
Cross section	18 mm^2
Electric connection type	Pin
Features	Can be cut to size Insulated
Functions	Busbar
Heat dissipation capacity	0 W
Heat dissipation per pole, current-dependent	0 W
Number of modular spacings	1
Number of phases	1
Number of poles	Single-pole
Pitch dimensions	17.6 mm
Rated conditional short-circuit current (Iq)	0 kA
Rated operational voltage (Ue) - max	1000 V
Rated short-time withstand current (Icw)	0 kA
Rated surge voltage	10 kV
Rated uninterrupted current (Iu)	80 A
Static heat dissipation, non-current-dependent	0 W
Suitable for number of devices	0
Type	Z-BB/UL Busbar
Used with	Z-BB/UL Busbar

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])

Number of phases		1
Number of poles		1
Suitable for number of devices		0
Module width	mm	17.6
Cross section	mm^2	18

Length		mm	1009.8
Can be cut to size			Yes
Width in number of modular spacings			1
Rated permanent current Iu		A	80
Type of electric connection			Pin
Insulated			Yes
Rated surge voltage		kV	10
Conditioned rated short-circuit current Iq		kA	0
Max. rated operation voltage Ue		V	1000
Rated short-time withstand current Icw		kA	0
Suitable for devices with N-conductor			No
Suitable for devices with auxiliary switch			No
Colour			Other

© 04/2023 by Eaton Industries GmbH