Special Products



ATO® Resistor

Part Number: 02400100_ series

Specifications

Operating Temp.:	-20˚C to +85˚C
Resistor Value:	Optional
Power Rating:	1/4 W Max
Body Material:	Thermoplastic
Term. Material:	C.R.S. (Ni/Zn Plated)
Term. Retention:	25 N



ATO® Diode **Part Number:** 02400103_ (Z = 1500 / LXN = 50)

1 A Diode in ATO® size housing. The cathode connector is rotated 90°

1-A-Diode in ATO®-Größe mit 90°-abgewinkeltem Kathodenanschluss.

Operating Temp.:	-40˚C to +85˚C
Diode Rating:	1.0 A
Max P.I.V.:	Optional
Body Material:	Thermoplastic
Term. Material:	C.R.S. (Ni/Zn Plated)
Term. Retention:	25 N



MINI® Resistor

Part Number: 02400100_ series

Operating Temp.:	-40˚C to +85˚C
Resistor Value:	Optional
Power Rating:	1/4 W Max
Body Material:	Thermoplastic
Term. Material:	C.R.S. (Ni/Zn Plated)
Term. Retention:	25 N



MINI® Diode

Part Number: 02400113_ (P= 2000 / LXN = 50)

Operating Temp.:	-40˚C to +85˚C
Diode Rating:	1.0 A
Max P.I.V.:	Optional
Body Material:	Thermoplastic
Term. Material:	C.R.S. (Ni/Zn Plated)
Term. Retention:	25 N



ATO® Shunt

Part Number: 02400094P (2000 pcs)

Operating Temp.:	-40˚C to +125˚C
Maximum Continuous Load Rating:	35A
Body Material:	Thermoplastic (UL 94V0 Rated)
Term. Material:	Brass Tin Plated



MINI® Shunt

Part Number: 0297900.WXNV (3000 pcs)

MINI® size shunt for continuous load up to 20A.

Shunt in MINI®-Bauform für Dauerlasten bis 20A.

Operating Temp.:	-40˚C to +125˚C
Maximum Continuous Load Rating:	20A
Body Material:	Thermoplastic (UL 94V0 Rated)
Term. Material:	Zinc Silver Plated



JCASE® Shunt

Part Number: 0495900.Z

Operating Temp.:	-40˚C to +125˚C
Maximum Continuous Load Rating:	50A
Body Material:	Nylon
Term. Material:	Copper

© 2006 Littelfuse • Automotive Circuit Protection Products