TECHNICAL SPECIFICATION

Swiss One RIGI

1RIGBB21AR / 1RIGBB21AR



DESCRIPTION

The best seller of the coming decade.. !
Whatever your workplace environment, RIGI delivers the perfect association of performance, safety and active style.
The unique close fitting design, ultra light weight… 19 grams of comfort and fit. Wide field of vision and a design fitting all faces…The ergonomic fit with FlexoFit temples, flat and thin compatible with any ear defender or helmet. Those features enable wearers to achieve a comfortable customised fit, throughout the day. Try it… adopt it!
Available in a wide range of lens versions… Anti-scratch, Excellence coating and a unique selection of Blue Blocker lenses

OPTIONS

1RIG23CKN (1RIG23CKN)
1RIG23SKN (1RIG23SKN)
1RIGBB21AR (1RIGBB21AR)
1RIGBB21LB (1RIGBB21LB)
1RIGBB21LO (1RIGBB21LO)
1RIG21C (1RIG21C)
1RIG21S (1RIG21S)

SAFETY STANDARDS

EN 170 • EN 166

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacture's Trademark Swiss One
Swiss One

Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ˚ Maximum protection for glasses
F

Blue Blocker Anti- Reflective Lens
Yes

Vision+ Lens
96% Visual Clarity

Lightweight
Yes

FLEXoFIT Technology
Yes

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Lens Base Curve
9.5

Anti-Scratch Coating (21 Code)
Yes

Soft End Tips - Flex Flat Temple Pressure Free
Yes

Product Weight
19g

FEATURES



Anti-mist

Anti-mist



Anti-scratch

Anti-scratch



Lens Curve

Lens curve



High Performance Coating

Anti-scratch / anti-fog high performance coating



Lightweight

Lightweight



Soft End Tips

Soft end tips



UV 400 Absorption

UV 400 absorption



Flexofit Technology

Flexofit technology

RANGE

SWISS ONE

DOWNLOADS

Image Pack (ZIP)
doc-rigi.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.