SSTB203008-316

Terminal box, 200x300x80

The stainless steel terminal box range, SSTB, with a IP 66 protection degree, is available off the shelf in many different sizes. The SSTB range is well suited for indoor and outdoor environments thanks to its corrosion resistance. Water and dust are prevented from entering the terminal box, thus eliminating the risk for component failure, and with that, unnecessary downtime.

Feature:
IP 66 TYPE 4X, 12 IK 08

CE UKCA cULus_UL Listed EAC GOST



CHARACTERISTICS

Height	200 mm
Width	300 mm
Depth	80 mm
Weight (kg)	2.25

Item no.: SSTB203008-316
EAN no.: 8713574200531

Technical data

Material: AISI 304L pre-grained stainless steel / AISI 316L (on request). Body: 1 mm. Cover: 1.5 mm.

Body: Folded and seam welded. Four M6x13 studs for bottom profile / mounting plate fixation. For ease of installation, each back corner of the enclosure is laser-marked to precisely indicate where to drill holes and affix AWS wall mounting brackets.

Gasket: Sealing is ensured by an injected polyurethane gasket. For AISI 316L, sealing is ensured by an injected silicone gasket.

Earthing: M8x18 mm earthing studs in body and cover, M8 nuts, earthing washers and earthing labels.

Protection: IP 66 | TYPE 4X, 12 | IK 08.

Finish: 400 pre-grained stainless steel.

Delivery: Body, cover, cover screws, fixing screws, cover plugs and earthing facilities.

Features

Feature: Stainless steel 304 and 316(L) terminal boxes, available in a wide range of sizes, with a high IP66 protection degree.

Advantage: Customers can choose terminal boxes that meet their size requirements, off the shelf. The installed components inside the terminal box will be safe and secure due to the high protection degree.

Benefit: Customers can receive terminal boxes with a short delivery time, that match their size requirements which can be installed in both indoor and outdoor environments due to the terminal box's excellent resistance to corrosion. This will also remove any extra costs due to oversizing. Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box.

Comment:	The mounting plate, BMP, and DIN profiles, BDR, mounted on profiles, BPP, have to be ordered separately, in order to complete the installation of the terminal box.