**Technical Specifications**

# New Manyard Edge

## Description:

The Manyard edge has integrated shock absorber, integrated fall indicator and a new tubular design in green and black.
The Manyard edge has been tested on edge .








## References:

1017916(CS20+Scaff hook)
1017918(2xCS20)

## Features:

Webbing:
Raw material: Polyester
Width: 60 mm
Breaking strength: > 3000 daN

CS20 Karabiner:
Raw material: steel (1017918)/aluminium(1017916)
Opening: 18mm
Breaking strength: >2200 daN

Scaff hook:
Raw material: Aluminum
Opening: 63mm
Breaking strength: >2000 daN

Weight :
1017916:1.206kg
1017918:1.040kg
Breaking strength: >2500 daN

EN355:2002 & PR EN 354:2006

***LAW of 19 MARCH 93***

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com