PRODUCT-DETAILS

OS20PA1FUU3B

OS20PA1FUU3B Enclosed switch fuse



General Information

Extended Product Type	OS20PA1FUU3B
Product ID	1SCA022280R9290
EAN	6417019066028
Catalog Description	OS20PA1FUU3B Enclosed switch fuse
Long Description	The enclosure in the OS series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries should be drilled. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340004M0004

Dimensions

Product Net Width	180 mm
Product Net Height	280 mm
Product Net Depth / Length	150 mm
Product Net Weight	1.7 kg 3.75 lb

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 20 A (690 V) 20 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 20 A (690 V) 20 A
Conventional Thermal Current (I_{the})	20 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	690 V
Power Loss	at Rated Operating Conditions per Pole 1.3 W
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Fuse Size	A1
Fuse System	British Standard
Standards	IEC 60947-1, -3
Number of Poles	3
Cable Cross-Section	10 mm²
Cable Entry Position	Up/Down
Cable Outlets Per Side	Blank / Blank
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	1 NO, 1 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Position of Neutral Terminals	Top In - Bottom Out
Position of PE Terminals	Top In - Bottom Out
Fuse Type	BS

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC340009D2703
Instructions and Manuals	1SCC340004M0004
RoHS Information	1SCC311106D0201

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	212 mm
Package Level 1 Depth / Length	313 mm

Package Level 1 Height	191 mm
Package Level 1 Gross Weight	2.1 kg
Package Level 1 EAN	6417019066028

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch Fuses

