TECHNICAL SPECIFICATION

EVOLite® Badge Mid Peak Wheel Vented

White / AJB173-400-100



DESCRIPTION

EVOLite® safety helmet with a clear plastic ID card holder that fits standard business card size identification. Simple push and slide mechanism. A lamp bracket can be positioned at the top of the unit.

OPTIONS

Blue (AJB173-400-500)
Green (AJB173-400-300)
Orange (AJB173-400-800)
Red (AJB173-400-600)
White (AJB173-400-100)
Yellow (AJB173-400-200)

SAFETY STANDARDS

EN 397

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Mid

Lateral Deformation
Yes

Maximum Temperature
+50˚C

ABS Shell
Yes

Textile
Harness

Wheel Ratchet
Yes

Ventilation
Yes

Integrated Eyewear
Optional

BSI Kitemark
Yes

Optional 4 point chinstrap (EN397 Compliant)
Optional

Product Weight
341g

Impact Resistance
50 Joules

Resistance to Molten Metals and Hot Solids Helmets (optional)
Yes

Minimum Temperature
-40˚C

Recyclable
Shell

Depth Adjustment
3D Harness

Universal Accessories Slot
Yes

Reflective Option
Optional

ID card holder
Fitted

Optional 2 point chinstrap (EN397 & EN 812 compliant)
Optional

JSPCheck
Yes

Size
53-64cm

FEATURES



Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch™ slip ratchet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors, and ear defenders. EVOSpec® Integrated eyewear is also available.



ID Card Holder

Clear plastic ID card holder that fits standard business card size identification. Simple push and slide mechanism. A lamp bracket can be positioned at the top of the unit.



3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aerospace	Agricultural
Airports	Construction and Infrastructure
Facilities Management	Food and Drink Manufacturing
Hospitals, Healthcare & Pharmaceuticals	Manufacturing
Maritime	Transportation, Warehousing & Logistics
Utilities Contractors	

LOGO

- [x] Back
- [x] Sides

RANGE

DOWNLOADS

Image Pack (ZIP)

doc-invincible-evolite.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.