DOWNLIGHT BODO CCT

BODO24

24 W - 2650lm - 3000-4200-6500K





DIMENSIONS	A	B	C
1	50	215	



GENERAL INFORMATIONS	
Code	BODO24
Ean	8031453025816
Family	DOWNLIGHT BODO CCT
Technology	LED
Body material	PC+AL
Diffuser / lens material	PS
Operating temperature (° C)	-20 - +40

LIGHTING DATA	
CCT (K)	3000-4200-6500
Luminous)ux (lm)	2650
Beam (°)	100
Color rendering (CRI)	>80

TECHNICAL FEATURES	
Power (W)	24
Supply voltage (V) / Max (V)	220 / 240
Power frequency (Hz)	50/60
Hole diameter (mm)	200
Current consumption (mA)	180
Insulation class	2
Power factor	0,5
Dimmer compatibility	NO
Nominal life (h)	25000
Impact resistance (IK)	08

PACKAGING	
Packaging	BOX
Pack	20
Gross weight (Kg)	7.5
Net weight (Kg)	0.26

Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it

NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice

BOT LIGHTING
FOR A BRIGHT FUTURE

DOWNLIGHT BODO CCT

BODO24
24W - 2650lm - 3000-4200-6500K

• Recessed LED luminaire in thermoplastic material with integrated power supply
• Lightweight and ideal for false ceilings
• White body in thermoplastic and metal, with satin thermoplastic diffuser anti glare
• Complete with terminal for simplified wiring
• Selectable CCT



Bot Lighting srl con unico socio
Via Lombardia, 37/39 – 30030 Cazzago di Pianiga (VE) Italy - T. +39.041.51.29.411 – F. +39.041.51.01.715
www.botlighting.it – ordini@botlighting.it – info@botlighting.it
NOTE: dati soggetti a modifiche senza preavviso | NOTE: data subject to change without notice