Date: 11/04/2023

S73.100/A, 0...60°C, L1=without,

Gas actuated thermometer, stainless steel series

Item number:	48783632
Quantity:	1 pcs.
Order code:	S73.100-C1C-AAF-ZZZZZ-ZZZ-Z-Z-HZZ-AHAZZZ G5 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
Overview:	S73.100/A, 0...60°C, L1=without, probe 120 x 22 x 12 mm, stainless steel axial laminated safety glass Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: S73.100, nominal size 100, adjustable stem and dial Unit: °C Scale range: 0 °C ... 60 °C Connection design: surface-mounted contact bulb for external mounting Process connection: probe 120 x 22 x 12 mm, stainless steel Insertion length L1: without Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.