DATASHEET - IZMX-RR110AD-40-1

Reset remote, 110-125VAC/DC

Part no.	**IZMX-RR110AD-40-1**
	184126
EL Number (Norway)	**4398489**

General specifications	
Product name	Eaton Moeller series IZMX/INX remote reset
Part no.	IZMX-RR110AD-40-1
EAN	4015081783243
Product Length/Depth	150 millimetre
Product height	100 millimetre
Product width	100 millimetre
Product weight	0.125 kilogram
Compliances	RoHS conform
Product Tradename	IZMX/INX
Product Type	Accessories
Product Sub Type	Remote reset
Delivery program	
Type	Accessory
Special features	The retrofit kit includes the required SEC control cable terminals. Cannot be combined with remote reset. After the remote reset coil is electrically actuated, the reclosing lockout can be reset. The circuit-breaker is equipped with a mechanical trip indicator (red pin).
Suitable for	Off-load switch Overload relay Power circuit breaker
Used with	IZMX40…W IZMX40…F
Technical Data - Electrical	
Voltage type	AC/DC
Control voltage operating range	110 - 127 V AC (50/60 Hz) 110 - 125 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min	110 V
Rated control supply voltage (Us) at AC, 50 Hz - max	127 V
Rated control supply voltage (Us) at AC, 60 Hz - min	110 V
Rated control supply voltage (Us) at AC, 60 Hz - max	127 V
Rated control supply voltage (Us) at DC - min	110 V
Rated control supply voltage (Us) at DC - max	125 V
Adjustment range undelayed short-circuit release (end value) - max	0 A
Power consumption	540 VA/W AC/DC
Initial value of the undelayed short-circuit release - min	0 A
Electric connection type	Flat plug-in connection
Technical Data - Mechanical	
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0
Design verification as per IEC/EN 61439 - technical data	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Additional information	
Accessory/spare part type	Trip indication / Reset options

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ecl@ss13-27-37-04-18 [AKF016018])			
Rated control supply voltage AC 50 Hz		V	110 - 127
Rated control supply voltage AC 60 Hz		V	110 - 127
Rated control supply voltage DC		V	110 - 125
Voltage type for actuating			AC/DC
Initial value of the undelayed short-circuit release - setting range		A	0
End value adjustment range undelayed short-circuit release		A	0
Power consumption		W	540
Type of electric connection			Flat plug-in connection
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Suitable for power circuit breaker			Yes
Suitable for off-load switch			Yes
Suitable for motor safety switch			No
Suitable for overload relay			Yes

© 04/2023 by Eaton Industries GmbH