Date: 12/04/2023

OLS-C01, G 1/2", Opened in media (SPST n.c.), Circular connector M8x1 3-pin

OLS-C01, G 1/2", Opened in media (SPST n.c.), Circular connector M8x1 3-pin

Item number:	14241206	
Quantity:	1 pcs.	
Order code:	OLS-C01-G1Z-HNCM8-ZZZZZ-ZZZ	W101OLS1Z1LC
Overview:	OLS-C01, G 1/2", Opened in media (SPST n.c.), Circular connector M8x1 3-pin Optoelectronic level switch for industrial applications Model: OLS-C01 Process connection: G 1/2" Output Signal: one switching output (PNP) Switch function: Opened in media (SPST n.c.) Power supply: 12 - 32 V DC Electrical connection: Circular connector M8x1 3-pin pin assignment el. connection: 1=U+, 3=U-, 4=SP Operating pressure: max. 25 bar Permissible medium temperature: -30…100 °C Wetted parts: Stainless steel 1.4571, borosilicate glass, silicone adhesive Specifications according to data sheet: LM 31.31	
Details:	OLS-C01, G 1/2", Opened in media (SPST n.c.), Circular connector M8x1 3-pin Optoelectronic level switch for industrial applications Model: OLS-C01 Process connection: G 1/2" Output Signal: one switching output (PNP) Switch function: Opened in media (SPST n.c.) Power supply: 12 - 32 V DC Electrical connection: Circular connector M8x1 3-pin pin assignment el. connection: 1=U+, 3=U-, 4=SP Operating pressure: max. 25 bar Permissible medium temperature: -30…100 °C Wetted parts: Stainless steel 1.4571, borosilicate glass, silicone adhesive Specifications according to data sheet: LM 31.31	

© 2023 - WIKA Instruments s.a.r.l.