PRODUCT-DETAILS

OTDC16F3

OTDC16F3 DC Switch-disconnector



General Information

Extended Product Type	OTDC16F3
Product ID	1SCA121457R1001
EAN	6417019526126
Catalog Description	OTDC16F3 DC Switch-disconnector
Long Description	OTDC16F3 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Base mounting, IEC 1000 VDC 16 A single circuit

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Estonia (EE)

Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301079M0206

Dimensions

Product Frame Size	XS

Product Net Width	52.5 mm 2.1 in
Product Net Height	89 mm 3.5 in
Product Net Depth / Length	77.6 mm 3.1 in
Product Net Weight	0.2 kg 0.4 lb

Technical

Rated Operational Current DC-21B (I_e)	(1000 V) 16 A
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 25 A
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity (I_{cm})	(1000 V DC) 0.8 kA
Rated Short-time Withstand Current (I_{cw})	(1000 V DC) 0.8 kA for 1 s 0.8 kA
Power Loss	at Rated Operating Conditions per Pole 0.15 W
Pollution Degree	3
Handle Color	Black
Handle Type	Knob handle
Shaft Diameter	6 mm 0.24 in
Switches Operating Mechanism	Mechanism on Top of the Switch
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Base mounting, DIN-rail mounting
Number of Circuits	1
Number of Poles	3
Cable Cross-Section	2.5 ... 16 mm²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	1.2 … 1.4 N·m
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B)

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	NA

Certificates and Declarations (Document Number)

CCC Certificate	CQC2012010302579872
Declaration of Conformity - CE	1SCC301192D2704
DNV GL Certificate	1SCC301231D0201
Environmental Information	NA
Instructions and Manuals	1SCC301079M0206
RoHS Information	1SCC301192D2704

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	100 mm 3.9 in
Package Level 1 Depth / Length	64 mm 2.5 in
Package Level 1 Height	100 mm 3.9 in
Package Level 1 Gross Weight	0.2 kg 0.5 lb
Package Level 1 EAN	6417019526126

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601352
E-Number (Sweden)	3134017

Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors

