Date: 24/04/2023

233.30.063 2.5 bar G1/4B lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number:	48795415
Quantity:	1 pcs.
Order code:	233.30-C-BG325Z-GB-UZHZCZN-AHAZZZZ 313D4GZIYG0 Z2Z-IZZZZZZ121ZZ LABEL-PG1DE-ZZZZZ
Overview:	233.30.063 2.5 bar G1/4B lower mount Measuring System 316 SS Ingress protection: IP 65 NACE Sour Gas Service Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) class 1.6 Window: laminated safety glass Case filling fluid: glycerine-water-mixture Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 … +60 °C Pressure Gauge Standard: International (standard Europe) stop-pin at zero *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 233.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: with Nominal size: 063 mm Measuring range: gauge pressure range Scale range: 0...2.5 bar Process connection: G 1/4 B Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Special design features: NACE Sour Gas Service Explosion protection: ATEX Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Accuracy class: class 1.6 Overpressure safe: standard Case material: Stainless steel 1.4301

© 2023 - WIKA Instruments s.a.r.l.

Case surface: bare
Material pressure element: Measuring System 316 SS
Case filling fluid: glycerine-water-mixture
Ingress protection: IP 65
Permissible medium temperature: + 100 °C
Permissible ambient temperature: -20 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
Manufacturer logo: *WIKA*
stop pin on dial: at zero
with Serial number
Ignition protection type: Ex h
Permissible ambient temperature: -20 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.