MURR ELEKTRONIK
stay connected

COMLIGHT56 LED CLEAR STATUS LIGHT

With 4 pole M12 bottom exit

Compact status light
Flange M12 male, 4-pole
clear

[Link to Product]

Illustration



Product may differ from Image

Commercial data	
ECLASS-6.0	27371220
ECLASS-6.1	27110390
ECLASS-7.0	27110390
ECLASS-8.0	27110390
ECLASS-9.0	27110350
ECLASS-10.1	27110350
ECLASS-11.1	27110350
ECLASS-12.0	27110350
ETIM-5.0	EC000232
customs tariff number	85319000
GTIN	4048879855747
Packaging unit	1
Electrical data | Supply	
Operating voltage DC	24 V
Current consumption max.	26 mA
Industrial communication | HMI	
Luminous intensity	1541 mcd
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Protection degree additional condition	inserted, locked

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-11-02

Mechanical data | Material data	
Material housing	Plastic
Mechanical data | Mounting data	
Height	78,8 mm
Width	56 mm
Depth	56 mm
Environmental characteristics | Climatic	
Operating temperature min.	-30 °C
Operating temperature max.	50 °C
Connection type 1	
Family construction form	M12
Gender	male
Coding	A
No. of poles	4
PIN 3	BU 0 V (24 V DC)
PIN 4	BK 24 V DC (0 V)

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2023-11-02