# Professional Cable Reel 300 KU 4100 IP 44, 40 m H07RN-F 3G1,5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use, IP 44.










MADE IN GERMANY | cable pilot | 5 YEARS MANUFACTURER GUARANTEE | DGUV-I 203-006 K2 | VDE 0100 Teil 704 | SPECIAL ROBUST | IP 44

| | |
|---|---|
| **Product number** | 9231400101 |
| **EAN** | 4007123688609 |

## DESCRIPTION

- Reel body made of special plastic on galvanised support frame.
- 5 splash-proof sockets with earthing contact, with self-closing lids.
- Innovative „cablepilot“ carrying handle for perfect cable routing. Swings on both sides for convenient carrying and hanging.
- With twist handle for convenient retraction.
- With drum brake.
- Category 2 equipment (K2 DGUV 203-005): Use for rough operation with high mechanical, physical and chemical impacts.
- RN cable is approved for harsh building conditions in accordance with VDE 0100 Part 704.
- Overheating protection with indicator light for overheating and overloading.
- With visual readiness indicator.

## TECHNICAL DATA

| | |
|---|---|
| **Cable quality** | Rubber-Neoprene |
| **Cable length** | 40 m |
| **Cable designation** | H07RN-F 3G1,5 |
| **Cable colour** | black |
| **Reel diameter** | 300 mm |
| **Plug system CEE socket** | Without |
| **Plug system socket** | Type F (Protective contact) |
| **Plug system plug** | Type E and F (Protective contact with earth hole) |
| **Max. current carrying capacity** | 16 A |
| **Nominal input voltage** | 230 V |
| **Degree of protection (IP)** | IP44 |

## PACKAGING, DIMENSIONS AND WEIGHTS

| | |
|---|---|
| **UP** | 1 |
| **Weight of product (without packaging)** | 7.61 kg |
| **Dimension LxWxH (without packing)** | 20 cm x 30 cm x 39.5 cm |
| **Weight of product (including packaging)** | 7.61 kg |
| **Dimension LxWxH (incl. packing)** | 20.5 cm x 31 cm x 40 cm |

## SCOPE OF DELIVERY

Professional Cable reel 300 KU 4100 IP44