MSCC-35-35-F

Ruland MSCC-35-35-F, 35mm x 35mm Rigid Coupling, Black Oxide Steel, Set Screw Style with Keyway, 67mm OD, 95mm Length







Description

Ruland MSCC-35-35-F is a set screw rigid coupling with 35mm x 35mm bores, 67mm OD, 95mm length, and 10mm x 10mm keyways. It has precision honed bores to ensure they are collinear and do not introduce misalignment or vibration into the system making it suitable for high precision servo appliactions as well as shaft to shaft connections. Forged screws test beyond DIN 912 12.9 standards to ensure maximum holding power. Tightly controlled bore tolerance of +.050mm/+.012mm is maintained. MSCC-35-35-F is made from 1215 lead-free steel with a proprietary black oxide finish that produces a fine glossy finish while increasing holding power and resisting corrosion. It is machined from solid bar stock that is sourced exclusively from North American mills and is RoHS3 and REACH compliant. MSCC-35-35-F is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	35 mm	**Small Bore (B2)**	35 mm
Keyway (K1)	10 mm	**Keyway (K2)**	10 mm
B1 Max Shaft Penetration	47.5 mm	**B2 Max Shaft Penetration**	47.5 mm
Bore Tolerance	+0.050 mm / +0.012 mm	**Outer Diameter (OD)**	67 mm
Length (L)	95 mm	**Recommended Shaft Tolerance**	+0.000 mm / -0.013 mm
Forged Set Screw	M8	**Screw Material**	Alloy Steel
Hex Wrench Size	4.0 mm	**Screw Finish**	Black Oxide
Seating Torque	17 Nm	**Number of Screws**	4 ea
Rated Torque	Rating Coming Soon	**Moment of Inertia**	1.344×10^{-3} kg-m^2
Maximum Speed	4,000 RPM	**Full Bearing Support Required?**	No
Precision Honed Bores?	Yes	**Zero-Backlash?**	Yes
Material Specification	1215 Carbon Steel Bar	**Temperature**	-40°F to 350°F (-40°C to 176°C)
Finish Specification	Hot Process Black Oxide, Impregnated with Naphthenic Oil, Centrifugally Dried	**Manufacturer**	Ruland Manufacturing
Country of Origin	USA	**Weight (lbs)**	4.117200
UPC	634529107867	**Tariff Code**	8483.60.8000
UNSPC	31163009		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	**WARNING** This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		

Installation Instructions

1. Align the MSCC-35-35-F set screw rigid coupling on the two shafts to be connected. There should be no misalignment.
2. Tighten the set screws in two stages, starting with the inside set screws. Using a 4.0 mm torque wrench, tighten the inside set screws to 8.5 Nm which is half the recommended seating torque. Repeat for the outside set screws, again tightening to half of the recommended seating torque.

3. Tighten the screws to the full recommended seating torque of 17 Nm following the same pattern, starting with the inside set screws first.