
Soldering Irons and Tips

Magnastat Controlled Low Voltage Soldering Irons

Soldering Tips for TCPS, TCP 12, TCP 24 and FE 50M (continued)



Order No.	Model	Description	Width A
4PTF7	**PT F7**	Round tip sloped 370°C	Ø 1,2 mm
4PTF8	**PT F8**	Round tip sloped 425°C	Ø 1,2 mm
4PTAA7	**PT AA7**	Round tip sloped 370°C	Ø 1,6 mm
4PTAA8	**PT AA8**	Round tip sloped 425°C	Ø 1,6 mm
4PTAA9	**PT AA9**	Round tip sloped 480°C	Ø 1,6 mm
4PTBB7	**PT BB7**	Round tip sloped 370°C	Ø 2,4 mm
4PTBB8	**PT BB8**	Round tip sloped 425°C	Ø 2,4 mm
4PTBB9	**PT BB9**	Round tip sloped 480°C	Ø 2,4 mm
4PTCC7	**PT CC7**	Round tip sloped 370°C	Ø 3,2 mm
4PTCC8	**PT CC8**	Round tip sloped 425°C	Ø 3,2 mm
4PTCC9	**PT CC9**	Round tip sloped 480°C	Ø 3,2 mm
4PTDD7	**PT DD7**	Round tip sloped 370°C	Ø 5,0 mm
4PTDD8	**PT DD8**	Round tip sloped 425°C	Ø 5,0 mm
4PTDD9	**PT DD9**	Round tip sloped 480°C	Ø 5,0 mm

If other temperature or tips are required use PT / LT adapter see page 101.

Weller WDC – Dry Cleaner



Order No.	Model	Description
005 15 124 99	**WDC**	**Weller WDC – Dry Cleaner** The solution for cleaning from lead free solder! For further information see page 182.
Accessory: 005 13 840 99		Brass wool WDC replacement (2 pieces)



Order No.	Model	Description
005 41 734 99	**DIL 16WG**	Desoldering tip for Dual-In-Line 310°C 7,62 x 2,54 mm



005 13 040 99	**DS 7**	Desoldering attachment 370°C
005 13 804 99		Spare tiplet for desoldering attachment DS 7, Ø 1,5 mm