CMA-360B

PRO MILLIAMP CLAMP METER

TESTING | TROUBLESHOOTING | ACCURACY



Product Features:

A clamp meter measuring into the milliampere range is a necessity in today's growing market of 2-wire irrigation. Testing and troubleshooting a variety of applications in the irrigation and landscape industry requires test equipment that can address multiple problems and environments.

The Tempo Communications CMA-360B True RMS Pro Milliamp Clamp Meter is useful for testing/troubleshooting applications for 2-wire irrigation systems, traditional irrigation system wiring, pump wiring, landscape lighting and a wide variety of electrical applications. Auto-Ranging takes the guesswork out of the equation, simply set the meter to the appropriate position on the dial to test AC volts, DC volts, Current, Milliamp current or Ohms. True RMS gives the user the ability to obtain accurate results in "dirty" power conditions, measuring current draw of a pump motor for example. Combine the True RMS with resistance measurement up to 600k Ohms and current measurement resolution to 1/1000th of a milliamp, one microamp, provides the ability to find troubles other meters may miss.

Typical uses of the Pro Milliamp Clamp CmA-360B

- mA current measurement for 2-wire irrigation
- Voltage and resistance measurements for irrigation/ landscape lighting wiring systems
- Current measurements for pumps, lighting systems, etc.

Features

- True RMS
- Backlit display
- Auto-ranging
- 0.001 mA (1 µA) current resolution
- Auto Power Off
- Includes case and 2 x AAA batteries

CAT. NO.	UPC NO.	DESCRIPTION
CMA-360B	810025410995	Pro Milliamp Clamp Meter

FUNCTION	RANGE	RESOLUTION	ACCURACY
ACmA	6.000mA/60.00mA/600.0mA	1 µA/10 µA/100 µA	± 1%rdg ± 3dgts
ACA	6.000A/60.00A	0.001A/0.01A	± 1%rdg ± 3dgts
DCV	60V/600V	0.01V/0.1V	±1%rdg ± 2dgts
ACV	60V/600V	0.01V/0.1V	± 1%rdg ± 3dgts
Ohms	600Ω/6KΩ/60KΩ/600KΩ	0.1Ω/1Ω/10Ω/100Ω	±1%rdg ± 2dgts
Continuity Test Sound Level	< 60Ω		----

DISPLAY:	4 digit Liquid display, Maximum reading 6000
SAMPLING RATE:	2 times/sec
BATTERY:	1.5V size AAA battery x 2
DIMENSIONS:	8.1 in x 2.9 in 1.3 in (206 mm x 76 mm x 33.5 mm)
WEIGHT:	0.6 lb (0.27 kg)
MAXIMUM JAW OPENING:	ø 0.9 in (23 mm)

1390 Aspen Way Vista, CA • 92081
Latin America Phone : 1 760 510 0558 | EMEA Phone: +44 (0) 1633 927 050
India and SAARC Region Sales: indiaSales@tempocom.com

EMEA: Tempo Europe Limited • Brecon House
William Brown Close • Cwmbran • NP44 3AB • UK

TC-CMA360B 03/23

©2022 Tempo Communications Inc. • An ISO 9001 Company

Follow us **@TempoComms**

TEMPO COMMUNICATIONS

Renewed Vision. Innovation Forward.

TempoCom.com | tel 800.642.2155