Date: 11/04/2023

LME-AV4FVEN65/6/B1-VK5/T15-L300/14-V52R

LME-AV4FVEN65/6/B1-VK5/T15-L300/14-V52R

Item number: 48748294

Quantity: 1 pcs.

Order code: FLR-CBMZE001020850D4ZE2ZZEGAA03000026AN2#
KLVIR5A0242ZZ
CERT22-EG82-AA- - - - - - - - - - -
APPROVAL-FLR-RU01-ZZZZ-ZZZZ-ZZZZ

Overview: LME-AV4FVEN65/6/B1-VK5/T15-L300/14-V52R
Magnetic Level Transmitter Type FLR-SB
Pressure: 1 bar
Temperature range -30°C up to +100°C
Fluid density: 850 kg/m³
Material: Stainless steel 316Ti (EN 1.4571)
Housing: Stainless steel
Ingress protection: IP66/68
Electrical connection: M20 x 1.5 mm with cable gland
Output signal: 4-20 mA
Head mounted transmitter: T15.HZ - 2 wire, standard
Process connection: Flange DIN EN 1092-1 DN 65 PN 6 Form B1
Float: Stainless steel 316Ti V52R; Float outer diameter: 52 mm
Guide tube: OD 14 mm Insertion length (L): 300 mm
100% level position (L1): 26 mm
Measuring range: 242 mm
Contact separation: 5 mm
Tube end: Float collar
***
Additional ordering information: Etiquette spéciale : E00D19300REVB / DEXIS /
Item : 244487

Float fits through the connection nozzle

Test report 2.2 per EN 10204
Certificate Language: English and German
Certificate for: Float level transmitter
Formal certificate: Manufactured according to the state of the art
Magnetic Level Transmitter
Russia EAC (Import) + GOST (Metrology) + Technical Passport

Details: LME-AV4FVEN65/6/B1-VK5/T15-L300/14-V52R
Magnetic Level Transmitter Type FLR-SB
Pressure: 1 bar
Temperature range -30°C up to +100°C
Fluid density: 850 kg/m³

© 2023 - WIKA Instruments s.a.r.l.

Material: Stainless steel 316Ti (EN 1.4571)
Housing: Stainless steel
Ingress protection: IP66/68
Electrical connection: M20 x 1.5 mm with cable gland
Output signal: 4-20 mA
Head mounted transmitter: T15.HZ - 2 wire, standard
Process connection: Flange DIN EN 1092-1 DN 65 PN 6 Form B1
Float: Stainless steel 316Ti V52R; Float outer diameter: 52 mm
Guide tube: OD 14 mm Insertion length (L): 300 mm
100% level position (L1): 26 mm
Measuring range: 242 mm
Contact separation: 5 mm
Tube end: Float collar
***
Additional ordering information: Etiquette spéciale : E00D19300REVB / DEXIS / Item : 244487

Float fits through the connection nozzle

Test report 2.2 per EN 10204
Certificate Language: English and German
Certificate for: Float level transmitter
Formal certificate: Manufactured according to the state of the art

Russia: EAC (Import) + GOST (Metrology) + Technical Passport
Product designation: Magnetic Level Transmitter

© 2023 - WIKA Instruments s.a.r.l.