PLATESWITCHES

Neon Locator

Side Access, Captive Terminal Screws

Top Access, Backed out and Captive Terminal screws

10 AMP FLUSH

10 AMP FLUSH

20 AMP FLUSH

10 AMP FLUSH





K3041



K4870GRA



K4871WHI



K4872WHI



K4872GRA



K4875WHI



K4873WHI



K4874WHI



K4879WHI



K4870D2WHI



K4871D2WHI



K4872D2WHI



K4878BWHI



K4878PWHI

K3041 5
NEON PLATESWITCH LOCATOR
200-250V. 50Hz.
TUNGSTEN GLS LAMPS ONLY

K4870WHI 10
K4870GRA 10
1 GANG SP
ONE-WAY

K4871WHI 10
K4871GRA 10
1 GANG SP
TWO-WAY

K4872WHI 10
K4872GRA 10
2 GANG SP
TWO-WAY

K4875WHI 10
1 GANG
INTERMEDIATE

K4876WHI 10
1 GANG DP
ONE-WAY

K4873WHI 10
3 GANG SP
TWO-WAY

K4874WHI 5
4 GANG SP
TWO-WAY

K4879WHI 5
6 GANG SP
TWO-WAY

K4870D2WHI 10
1 GANG SP
ONE-WAY

K4871D2WHI 10
1 GANG SP
TWO-WAY

K4872D2WHI 10
2 GANG SP
TWO-WAY

K4878BWHI 10
1 GANG SP
TWO WAY
PUSH SWITCH WITH BELL SYMBOL
PUSH TO MAKE OR BREAK

K4878PWHI 10
1 GANG SP
TWO WAY
PUSH SWITCH MARKED 'PRESS'
PUSH TO MAKE OR BREAK

Neon Plateswitch Locator is for use with any 1, 2 and 3 gang Logic Plu™ plateswitches.

Used for location of switches in dark situations.

FIXING CENTRES: 60.3mm

BS 5733: 2010

MOUNTING BOXES:

FLUSH:
1, 2 & 3 GANG: 3995ZIC
4 & 6 GANG: 862ZIC

SURFACE:
1, 2 & 3 GANG: K2160WHI
4 & 6 GANG: K2161WHI

These switches do not have to be derated when used with fluorescent or inductive loads.

K4871, K4872, K4873, K4874, K4879
These switches can be wired as either one-way or two-way.

DIMENSIONS:
1, 2 & 3 gang: 86 x 86mm
4 & 6 gang: 86 x 146mm

FIXING CENTRES:
1, 2 & 3 gang: 60.3mm
4 & 6 gang: 120.6mm

BS EN 60669-1: 1999

20A VERSIONS
K4870, K4873, K4874, K4875, K4871 & K4872 are all available as 20A SP versions. Use suffix D2WHI when ordering.

K4867WHI
is 20A DP 1 way version of K4871.

K4868WHI
is 20A DP 1 way version of K4872.

MOUNTING BOXES:

FLUSH:
3995ZIC

SURFACE:
K2160WHI

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS EN 60669-1: 1999